

COOLMAX

Compact Cooling Units by WITTMANN

Wittmann

- » Powerful, compact air cooled chillers with 10 kW to 89 kW cooling capacity.
- » Reliable WITTMANN microprocessor controller
- » Large surfaced built-in air condenser with fan neck.
- » Automatic filling visual control via sight glass.
- » 3–7 bar centrifugal pumps with flow volume of 13.2 m³/hr.
- » Hermetically welded quality compressors
- » Anti-freeze control
- » Pressure relieve valve in the cooling circuit



COOLMAX 40

COOLMAX PERFORMANCE DATA

Model	Cooling capacity		Tank volume ltr	Water supply Ø	Flow rate m ³ /hr	Pressure bar	Dimensions mm	Weight kg
	kW	kcal/hr						
COOLMAX 30	10.0	8,600	41	1"	1.80	3.2	600 x 800 x 1,230	160
COOLMAX 40	14.5	12,470	41	1"	2.40	3.1	600 x 800 x 1,230	180
COOLMAX 50	19.0	16,340	41	1"	3.00	3.0	600 x 800 x 1,230	190
COOLMAX 70	23.5	20,210	55	1"	4.00	3.0	750 x 1,015 x 1,250	280
COOLMAX 80	26.0	22,704	55	1"	4.40	3.0	750 x 1,015 x 1,250	300
COOLMAX 100	38.0	32,938	120	1 1/4"	6.00	3.0	750 x 1,500 x 1,450	340
COOLMAX 120	45.0	38,528	120	1 1/4"	7.20	3.0	750 x 1,500 x 1,450	360
COOLMAX 150	52.5	45,150	220	1 1/2"	9.00	3.0	750 x 1,985 x 1,450	620
COOLMAX 200	78.0	67,424	220	1 1/2"	10.76	3.0	750 x 1,985 x 1,450	630
COOLMAX 250	89.0	76,798	220	1 1/2"	13.20	3.0	750 x 1,985 x 1,450	650

Specifications subject to change without notice.

- » For each model there are 3 to 7 bar pumps with larger flow rates available.
- » The pumps are protected with a motor protective relay and with a bypass line to prevent too high pressure in the line.
- » In the condenser the aluminum fins are generously spaced to prevent accumulation of dust.
- » Moreover the copper piping in the compressor line has few welded parts and is formed in order to prevent leakage.

world of innovation

WITTMANN Kunststoffgeräte GmbH
Lichtblaustrasse 10
1220 Vienna | Austria
Tel.: +43 1 250 39-0
info.at@wittmann-group.com

www.wittmann-group.com